

SimFlex Hybrid PUSealant Page 1 of 5

Section 1 - Identification of The Material and Supplier

Simseal PO Box 5280 Daisy Hill 41	info@simseal.com.au 27 QLD 1300 SILICONE	
Chemical nature:	Mixture	
Trade Name:	SimFlex Hybrid PU Sealant	
Product Use:	Adhesive, Sealant	
Creation Date:	July, 2023	
This version issued:	July, 2023	
Poisons Information Ce	entre: Phone 13 11 26 from anywhere in Australia	
	Section 2 - Hazards Identification	
Statement of Hazardo	ous Nature	
SUSMP Classification:	None allocated.	
ADG Classification: None allocated. UN Number: None allocated		
GHS Signal word: na		
Precautionary statements		

Other hazards

Emergency Overview

Physical Description & Colour: Mixture. Odour: Characteristic odour. Major Health Hazards: no significant risk factors have been found for this product.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc,%		
SILANE MODIFIED RESIN	216597-12-5	20 – 30		
DI-ISONONYL PHTHALATE (DOP Plasticizer)	117-81-7	15 - 35		
CALCIUM CARBONATE	471-34-1	50 - 70		
CARBON BLACK	1333-86-4	0 - 5		

Issued by: Simseal Product: SimFlex Hybrid PU Sealant 1300 SILICONE This version issued: July, 2023



SimFlex Hybrid PUSealant Page 2 of 5

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no

longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: Remove person to fresh air and keep comfortable for breathing

Skin Contact: Wash skin with plenty of water.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: Call a poison center or a doctor if you feel unwell.

Indication of any immediate medical attention and special treatment needed treat symptomatically.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: -

Extinguishing Media: Dry powder. CO2

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. **Flash point:** -

Section 6 - Accidental Release Measures

Emergency procedures :

Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. **Protective equipment :**

Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Avoid release to the environment.

Methods for cleaning up : Mechanically recover the product. **Other information :** Dispose of materials or solid residues at an authorized site.

Section 7 - Handling and Storage

Handling:

Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/ vapors/spray. Wear personal protective equipment.

Hygiene measures :

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Storage:

Store in a well-ventilated place. Keep cool.

Issued by: Simseal Product: SimFlex Hybrid PU Sealant 1300 SILICONE This version issued: July, 2023

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

SimFlex Hybrid PU Sealant

Page 3 of 5

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits

TWA (mg/m³) STEL (mg/m³)

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular without proper containment systems.

Ventilation: In case of insufficient ventilation, wear suitable respiratory equipment

Eye Protection: Safety glasses

Skin Protection: Wear suitable protective clothing

Protective Material Types: There is no data that enables us to recommend any type except that it should be impermeable.

Appropriate engineering controls : Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. See Section 7 for information about design of technical facilities.

Environmental exposure controls : Avoid release to the environment.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Paste
Odour:	No data.
Boiling Point:	No data.
Freezing/Melting Point:	No data.
Volatiles: Vapour Pressure:	No data.
Density:	No data.
Relative Density:	No data.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data.
Autoignition temp:	No data
Solubility:	Poorly soluble in water.
Flammability:	Non-Flammable.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: None known.

Incompatibilities: No particular Incompatibilities.

Fire Decomposition: No significant quantities of decomposition products are expected at temperatures normally achieved in a fire. No dangerous decomposition products known.

Polymerisation: This product will not undergo polymerisation reactions.

Hazardous Combustible Products: Carbon oxide.

Section 11 - Toxicological Information

Local Effects: There is no data to hand indicating any particular target organs. Target Organs:

May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled

Issued by: Simseal Product: SimFlex Hybrid PU Sealant 1300 SILICONE This version issued: July, 2023

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)





SimFlex Hybrid PU Sealant Page 4 of 5

Section 12 - Ecological Information

Ecology - general :

The product is not considered harmful to aquatic organisms nor to

cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term:Not classified(acute)Hazardous to the aquatic environment, long-term:Not classified(chronic)Classification procedure:Not classified

Section 13 - Disposal Considerations

Disposal: Dispose of contents/container in accordance with licensed collector's sorting instructions. Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program (USA)
R-Phrase SUSMP UN Number	Risk Phrase Standard for the Uniform Scheduling of Medicines & Poisons United Nations Number

Issued by: Simseal Product: SimFlex Hybrid PU Sealant 1300 SILICONE This version issued: July, 2023



SimFlex Hybrid PU Sealant Page 5 of 5

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H333	May be harmful if inhaled
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Disclaimer: This Certificate provides restrictions for use of the specified product based only on those materials restricted by IFRA Standards for the toxicity endpoint(s) described in each Standard. This Certificate does not provide certification of a comprehensive safety assessment of all product constituents.

SDS EU (Final)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable

Issued by: Simseal Product: SimFlex Hybrid PU Sealant 1300 SILICONE This version issued: July, 2023

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)