

CARPET GRIP

SOLVENT BASED ADHESIVE

Description

Carpet Grip is a cost-effective solvent-based adhesive specially formulated for carpet bonding. It is easy to spread and it grabs immediately upon contact. It's easy to use and it offers good bonding strength.

Properties

- Cost effective
- Specially for carpet bonding
- Excellent adhesion

Technical Data

PROPERTY	VALUE
Solids Content:	27 – 29 %
Specific gravity:	0.82 – 0.86
Viscosity at 25°C	1,400 – 1,700 cPs Brookfield LV2, 20 rpm



Application

Ideal for carpet bonding, also bonds most other materials such as Formica, rubber, cork, leather, fiberglass, polyurethane foam, EVA to wood, metal or concrete.

Application Direction

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Stir adhesive before use.
3. Apply the adhesive to both surfaces to be bonded with a dry, clean brush or scraper to give a uniform coating.
4. Allow the solvents to evaporate until the adhesive film is touch dry. It will take between 5 to 20 minutes depending upon surface porosity and weather condition.
5. Position the coated surfaces accurately before assemble them. Apply even pressure to consolidate the bond.

Physical State

Yellowish brown

Packaging

3.0 L/ tin (8 tins/carton)

Open Time

5 to 20 minutes

Application Temperature

-10 °C to 40 °C

Service Temperature

-10 °C to 60 °C

Shelf Life

12 months

Storage

Highly flammable, keep away from heat source or naked flames. Store in dry and cool place, below 30 °C.

Caution

Highly flammable liquid and vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Wear protective gloves. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Store in a well-ventilated place. Keep cool. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Legal Notes

Simseal® has made every effort to ensure accurate information but cannot be held liable for any losses or damages arising from its use, due to uncontrollable variations in processing and workmanship. Users should verify the product's suitability through their own testing.



YELLOWISH BROWN