

Roof, Glass & Gutter Silicone Sealant

Page 1 of 5

# Section 1 - Identification of The Material and Supplier

<b>Simseal</b> PO Box 5280 Daisy Hill 412	info@simseal.com.au 7 QLD 1300 SILICONE		
Chemical nature:	Mixture		
Trade Name:	Roof, Glass & Gutter Silicone Sealant		
Product Use:	Silicone Sealant		
Creation Date:	1 November 2022		
This version issued:	1 November 2022		
Poisons Information Cen	tre: Phone 13 11 26 from anywhere in Australia	3	
	Section 2 - Hazards Identification		
Statement of Hazardous H317 - May cause an allergic skin re H412 - Harmful to aquatic life with to SUSMP Classification: None ADG Classification: None UN Number: None allocated	eaction ng lasting effects	•	(!)
GHS Signal word: Warni	ng		$\mathbf{v}$
<ul> <li>P101 - If medical advice is needed, have product container or label at hand.</li> <li>P102 - Keep out of reach of children.</li> <li>P103 - Read carefully and follow all instructions.</li> <li>P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> <li>P273 - Avoid release to the environment.</li> </ul>			
P337: If eye irritation persists P301+P330+P331: IF SWAL	s: seek medical attention. P352: Wash with plenty of soap and wa LOWED: Rinse mouth. Do NOT induce vomiting. e. Use extinguishing media suited to burning materials.	ater.	
STORAGE P403+P233: Store in a well- DISPOSAL	ventilated place. Keep container tightly closed.		
P501: If product can not be recycled, consider controlled incineration, or contact a specialist waste disposal company (see Section 13 of this SDS).			
Emergency Overview			
Odour: Characteristic odour	<b>olour</b> : Paste - supplied in various colours. significant risk factors have been found for this produc	t.	
Section 3 - Composition/Information on Ingredients			
Ingredients		CAS No	Conc,%
BUTAN-2-ONE O,O',O"-(METHYLS	LYLIDYNE)TRIOXIME	22984-54-9	1 – 10
BUTAN-2-ONE 0,0',0"-(VINYLSILYLIDYNE)TRIOXIME 2224-33-1 0.1 –		0.1 – 1	
N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE 1		1760-24-3	0.1 – 1

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no

Issued by: Simseal Product: Roof, Glass & Gutter Silicone Sealant

1300 SILICONE This version issued: 1 March 2023

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



# Safety Data Sheet Roof, Glass & Gutter Silicone Sealant

Page 2 of 5

# **Section 4 - First Aid Measures**

## **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

First-aid measures after inhalation : First-aid measures after skin contact :	Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs - get medical advice/attention.
First-aid measures after eye contact :	Rinse eyes with water as a precaution.
First-aid measures after ingestion :	Call a poison center or a doctor if you feel unwell.

# Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards**: This product is classified as a C1 combustible product. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

No fire decomposition products are expected from this product at temperatures normally achieved in a fire. **Extinguishing Media:** Water spray. Dry powder. Foam.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point:	No data.
Upper Flammability Limit:	No data.
Lower Flammability Limit:	No data.
Autoignition temperature:	No data.
Flammability Class:	No data.

### Section 6 - Accidental Release Measures

#### **Emergency procedures :**

Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### For emergency responders :

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### Avoid release to the environment.

Methods for cleaning up :	Mechanically recover the product.
Other information :	Dispose of materials or solid residues at an authorized site.

### Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: : Store in a well-ventilated place. Keep cool.



**Roof, Glass & Gutter Silicone Sealant** 

Page 3 of 5

# **Section 8 - Exposure Controls and Personal Protection**

The following Australian Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210. **SWA Exposure Limits** TWA (mg/m<sup>3</sup>) STEL (mg/m<sup>3</sup>) Exposure limits have not been established by SWA for this product. No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular without proper containment systems. Ventilation: Ensure good ventilation of the work station. **Eye Protection:** Safety glasses **Skin Protection:** Wear suitable protective clothing **Respirator:** In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls : Avoid release to the environment.

Section 9 - Physical and Chemical Properties:	
Physical Description & colour:	Solid Paste
Odour:	Characteristic odour.
Boiling Point:	No data.
Freezing/Melting Point:	No data.
Volatiles:	No data.
Vapour Pressure:	No data.
Relative Density:	≈ 1.02
Specific Gravity:	No data.
Water Solubility:	insoluble in water
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	No data.
VOC:	≈ 43.68 g/l

# Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: None known.

Incompatibilities: No particular Incompatibilities.

**Fire Decomposition:** No significant quantities of decomposition products are expected at temperatures normally achieved in a fire. No dangerous decomposition products known.

**Polymerisation:** This product will not undergo polymerisation reactions.

# Section 11 - Toxicological Information

#### Local Effects: Target Organs:

There is no data to hand indicating any particular target organs.

Issued by: Simseal Product: Roof, Glass & Gutter Silicone Sealant 1300 SILICONE This version issued: 1 March 2023



Roof, Glass & Gutter Silicone Sealant

Page 4 of 5

### **Classification of Hazardous Ingredients**

Ingredient

Risk Phrases

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.

#### N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE (1760-24-3)

LD50 Oral	2295 mg/kg
LD50 Dermal	2000 mg/kg
STOT- single exposure	May cause respiratory irritation.

#### BUTAN-2-ONE O,O',O''-(VINYLSILYLIDYNE)TRIOXIME (2224-33-1)

LD50 Oral	> 2000 mg/kg
LD50 Dermal	≈ 2009 mg/kg
STOT- repeated exposure Ma	y cause damage to organs through prolonged or repeated exposure.

#### BUTAN-2-ONE O,O',O"-(METHYLSILYLIDYNE)TRIOXIME (22984-54-9)

LD50 Oral	≈ 2453 mg/kg	
LD50 Dermal	> 2000 mg/kg	
STOT- repeated exposure May cause damage to organs through prolonged or repeated exposure.		

Skin corrosion/irritation :	Not classified	
Serious eye damage/irritation :	Not classified	
Respiratory or skin sensitisation :	May cause an allergic skin reaction.	
Section 12 - Ecological Information		
Ecology - general : Hazardous to the aquatic environment,	Harmful to aquatic life with long lasting effects. <b>short–term:</b> Not classified	

Hazardous to the aquatic environment, short-term: (acute) Hazardous to the aquatic environment, long-term: (chronic) Classification procedure:

#### Calculation method

Harmful to aquatic life with long lasting effects.

#### Section 13 - Disposal Considerations

**Disposal:** Dispose of contents/container in accordance with licensed collector's sorting instructions.

#### Section 14 - Transport Information

**UN Number:** This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

### Section 15 - Regulatory Information

AICS: This product is believed to be compliant with NICNAS regulations.

#### **Section 16 - Other Information**

#### This SDS contains only safety-related information. For other data see product literature.

Acronyms:
ADG Code
AICS
SWA
CAS number
IARC

NTP

Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> edition) Australian Inventory of Chemical Substances Safe Work Australia, formerly ASCC and NOHSC Chemical Abstracts Service Registry Number International Agency for Research on Cancer National Toxicology Program (USA)

Issued by: Simseal Product: Roof, Glass & Gutter Silicone Sealant 1300 SILICONE This version issued: 1 March 2023

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



**Roof, Glass & Gutter Silicone Sealant** 

Page 5 of 5

R-Phrase SUSMP UN Number	Risk Phrase Standard for the Uniform Scheduling of Medicines & Poisons United Nations Number
H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)