Simtack Pro Contact Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 21/10/2020 Revision date: 30/07/2021 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Simtack Pro Contact Adhesive
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use,Consumer use
Use of the substance/mixture : Adhesives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Simseal Pty Ltd
Unit 8/33-43 Meakin Road
Meadowbrook
QLD, 4131
E: info@simseal.com.au
P: 1300 SILICONE

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS02 GHS07 GHS08

Signal word (CLP) : Danger

Contains	:	toluene; P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN; rosin; colophony; ethyl acetate; NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
Hazard statements (CLP)	:	H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness. H361 - Suspected of damaging fertility. Suspected of damaging the unborn child. (inhalation). H373 - May cause damage to organs (nervous system, central nervous system) through prolonged or repeated exposure (inhalation). H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P321 - Specific treatment (see supplemental first aid instruction on this label).

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms (CLP) :

GHS02 GHS07 GHS08

Signal word (CLP)	:	Danger
Hazardous ingredients	:	toluene; P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN; rosin; colophony; ethyl acetate; NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
Hazard statements (CLP)	:	H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness. H361 - Suspected of damaging fertility. Suspected of damaging the unborn child. (inhalation). H373 - May cause damage to organs (nervous system, central nervous system) through prolonged or repeated exposure (inhalation). H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P321 - Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
toluene substance with a Community workplace exposure limit	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	30 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	(CAS-No.) 64742-49-0	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	(CAS-No.) 25085-50-1 (EC-No.) 607-533-3	1 – 10	Skin Sens. 1, H317
ethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	1 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
rosin; colophony	(CAS-No.) 8050-09-7 (EC-No.) 232-475-7 (EC Index-No.) 650-015-00-7	0.1 – 1	Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Water spray.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOELV TWA (mg/m³)	192 mg/m³
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m³)	384 mg/m³
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	TLV® Basis: Visual impair; female repro; pregnancy loss. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
Local name	TOLUENE
Biological Exposure Indices (BEI)	0.3 mg/g creatinine Parameter: o-Cresol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: B 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek
Regulatory reference	ACGIH 2020

ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOELV TWA (mg/m³)	734 mg/m³
IOELV TWA (ppm)	200 ppm
IOELV STEL (mg/m³)	1468 mg/m³
IOELV STEL (ppm)	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH TWA (ppm)	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2020

rosin; colophony (8050-09-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (mg/m³)	≈ 0.05 mg/m³
WEL STEL (mg/m³)	≈ 0.15 mg/m³

Exposure limit values for the other components

cyclohexane (110-82-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Cyclohexane	
IOELV TWA (mg/m³)	700 mg/m³	
IOELV TWA (ppm)	200 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
USA - ACGIH - Occupational Exposure Limits		
Local name	Cyclohexane	
ACGIH TWA (ppm)	100 ppm	
Remark (ACGIH)	TLV® Basis: CNS impair	
Regulatory reference	ACGIH 2020	

n-hexane (110-54-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Hexane	
IOELV TWA (mg/m³)	72 mg/m³	
IOELV TWA (ppm)	20 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
USA - ACGIH - Occupational Exposure Limits		
Local name	n-Hexane	
ACGIH TWA (ppm)	50 ppm	
Remark (ACGIH)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI	
Regulatory reference	ACGIH 2020	
USA - ACGIH - Biological Exposure Indices		
Local name	n-HEXANE	
Biological Exposure Indices (BEI)	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift	
Regulatory reference	ACGIH 2020	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):

8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Brown.
Odour	:	Characteristic.
Odour threshold	:	No data available
pH	:	Not applicable
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	> 68 °C
Flash point	:	< 23 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapour pressure	:	No data available
Relative vapour density at 20 °C	:	No data available
Relative density	:	≈ 0.88

Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	> 40 mm²/s
Viscosity, dynamic	:	7000 – 8000 cP
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Skin corrosion/irritation	:	Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	:	Not classified pH: Not applicable
Respiratory or skin sensitisation	:	May cause an allergic skin reaction.
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Suspected of damaging fertility. Suspected of damaging the unborn child. (inhalation).
STOT-single exposure	:	May cause drowsiness or dizziness.

toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.

ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs (nervous system, central nervous system) through prolonged or repeated exposure (inhalation).

toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Simtack Pro Contact Adhesive	
Viscosity, kinematic	> 40 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Not rapidly degradable

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1133	UN 1133	UN 1133	UN 1133	UN 1133
14.2. UN proper shipping name				
ADHESIVES (containing flammable liquid)	ADHESIVES (containing flammable liquid)	Adhesives (containing flammable liquid)	ADHESIVES (containing flammable liquid)	ADHESIVES (containing flammable liquid)
Transport document description				
UN 1133 ADHESIVES (containing flammable liquid), 3, II, (D/E)	UN 1133 ADHESIVES (containing flammable liquid), 3, II	UN 1133 Adhesives (containing flammable liquid), 3, II	UN 1133 ADHESIVES (containing flammable liquid), 3, II	UN 1133 ADHESIVES (containing flammable liquid), 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 640D
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP8
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33

Orange plates	:	
Tunnel restriction code (ADR)	:	D/E
EAC code	:	•3YE

Transport by sea

Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP8
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-D
Stowage category (IMDG)	:	B
Properties and observations (IMDG)	:	Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
Special provisions (IATA)	:	A3
ERG code (IATA)	:	3L

Inland waterway transport

Classification code (ADN)	:	F1
Special provisions (ADN)	:	640D
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E2
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	1

Rail transport

Classification code (RID)	:	F1
Special provisions (RID)	:	640D
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001, IBC02, R001
Special packing provisions (RID)	:	PP1
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1, TP8
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE7
Hazard identification number (RID)	:	33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list ≥ 0,1 % / SCL
Contains no REACH Annex XIV substances
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioacumulative potential/ toxicity or persistence)
SZW-lijst van kankerverwekkende stoffen : rosin; colophony is listed
SZW-lijst van mutagene stoffen : rosin; colophony is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : toluene is listed

Denmark

Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H225;H315;H317;H336;H361;H373;H412>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.